



Vērtnes rāmis:

3D stieņu panelis I (50 x 200 mm, d - 4 mm),
rāmis sametināts no 40 x 40 mm caurulēm

Stabi:

Kvadrāt caurules ar plastmasas uzgali augšpusē. Caurules izmērs atkarīgs no vārtu platuma.

Vārtu komplektā iekļautas:

LOCINOX eņģes G90Z-M20, nodrošina iespēju atvērt 90 grādu leņķī
LOCINOX aizkritnis VSF

Citi piederumi:

OX plastmasas slēdzene LAKZ P1 un plastmasas atduris SMKL QF add
LOCINOX iekšējais aizkritnis SUBY

Automātiskie vārti:


BFT

Pieejamā apdare:

Karsti cinkots pārklājums, kas atbilst EN1461
Gruntēti un pulverkrāsoti jebkurā RAL tonī



LOCINOX plastmasas slēdzene LAKZ P1
Ekonomiskiem staigāšanas vārtiem, poliamida korpusā ar nerūsējošā tērauda mehānismu. Šī slēdzene iesakāma kā standarts visiem neliela izmēra vārtiem. 25 cm gara masīva nerūsējošā tērauda mēlīte nodrošina drošu vārtu aizslēgšanu.



LOCINOX aizkritnis VSF

Standarta aizkritņi ar inovatīvo atkārtējo fiksēšanas sistēmu. Aizkritnis tiek automātiski nobloķēts starp dubultajām vērtņēm.



LOCINOX iekšējais aizkritnis SUBY
Iekšējais alumīnija aizkritnis. Aizkritnis darbojas atdura augstumā. Estētisks risinājums visām dubultajām vērtņēm.



BFT



BFT

IZMĒRI

Atveramais platums	Augstums (mm)								
3000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
3500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
4000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
4500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
5000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
5500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
6000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
7000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430



Leaf Frame:

3D wire panel (50x200 mm, d-4 mm),
Frame welded from tubes 40x40 (mm)

Posts:

Square tubes with a plastic cap on top. The size of the posts depends on the width of the gate.

Gates include:

LOCINOX hinges G90Z-M20 allows to open 90 degrees
LOCINOX drop bolt VSF

Other accessories:

OX plastic lock LAKZ P1 and plastic keep SMKL QF add
LOCINOX internal drop bolt SUBY

Gate automatic:


BFT

Available finishes:

Hot Dipped Galvanised according to EN1461
Primed and powder coated in RAL colour



LOCINOX plastic lock LAKZ P1
Economical walking gate with polyamide housing and stainless steel mechanism. This lock is advised as a standard for all small gates. A massive stainless steel throw of 25 mm guarantees a secure locking.



LOCINOX drop bolt VSF
Standard dropbolts with the innovative Quick-fix system. The dropbolt is auto-locked between the double wings.



LOCINOX internal drop bolt SUBY
Internal aluminium dropbolt. The dropbolt is operated at keep-height. The aesthetical solution for all your double wings.



BFT



BFT

SIZES

Clear opening width	Height (mm)								
	1030	1230	1430	1530	1730	1930	2030	2330	2430
3000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
3500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
4000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
4500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
5000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
5500 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
6000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430
7000 (mm)	1030	1230	1430	1530	1730	1930	2030	2330	2430